



# GFE PRESS-RELEASE

## CHAMELEON Network

Manuals and data-sheets can be viewed or downloaded in [globalfire.pt](http://globalfire.pt)

- **INT-422-P2P-D/S** - RS422 Interfaces
- **INT-FO-P2P-D/S** - Fiber Optic Interfaces
- **INT-MIX-FO/RS422-P2P** - Mixed RS422 and Fiber Optic Interfaces



### REL-MOD (NEW)

**RELAY MODULE is a low power relay for isolated interface with 3rd party systems.**

The main application is to convert Conventional Sounder Panel Output into signal dry contact relay.

### VOX PA updated with a Class D Amplifier (NEW VERSION)

Our Power Amplifier Voice Sounder module has been updated and it is now available in our Dual Gang Box. It uses now a modern, High efficiency Class D amplifier circuit, capable of delivering 24W rms into a 8 ohm speaker, fully monitored and protected against faults with short-circuit protection, thermal protection as well as undervoltage, and DC protection. Faults are reported back to the addressable panel just as a normal device.



Please contact **Sales** for version release.



### AEROSOL TRIGGER ADAPTER (NEW)

It is now available the GFE AEROSOL TRIGGER. This is a Conventional Sounder Output (28V) to Low Voltage, High Current (3V @ 2 Amp) Output converter built in our Module Box format. Usually applied on our ORION EX Extinguish Output in order to trigger directly, low voltage condensed aerosol activator.

Please contact **Sales** for version release.



### DUAL GANG modules / DIN RAIL mount option (NEW)

It is now available the DIN RAIL MODULE mount option.

Please contact **Sales** for version release.

## GLOBAL FIRE EQUIPMENT S.A.

Sítio dos Barrabés, Armazém Nave Y, Caixa Postal 908-Z, 8150-016 São Brás de Alportel - PORTUGAL  
Tel: +351 289 896 560 • Sales: [sales@globalfire.pt](mailto:sales@globalfire.pt) • Technical Support: [techs@globalfire.pt](mailto:techs@globalfire.pt) • [www.globalfire.pt](http://www.globalfire.pt)